

12" SQUARE RETROFIT MOFLOW™ SUCTION OUTLET COVER

VGB Series

The AquaStar line of suction outlet covers, compliant with the Virginia Graeme-Baker Pool and Spa Safety Act (ANSI/APSP 16-2011 and NSF/ANSI 50-2009a)

FEATURES

For single or multiple drain use (see installation instructions)

Single – 3" sump depth Floor: 274 GPM at 1.3 fps Wall: 278 GPM at 1.3 fps

Floor/wall: 323.1 GPM at 1.5 fps Floor/wall: 215.4 GPM at 1.0 fps

When 1.0 or 1.5 fps installations are not required, always use the lower tested flow rate

69.1 square inch opening

Trademarked VGB compliance button easily identifies VGB 2008 compliant cover from on deck and underwater

#316 stainless steel screws


Manufactured from superior UV-resistant engineered polymers

Easily and safely retrofits to most brands' 1" deep existing frames

All components (cover, sump, screws) meet or exceed ANSI/APSP 16-2011 and NSF/ANSI 50-2009a national standards and ASTM G154 UV testing exposure

Replace every five years from the date of installation

10 per case



Fits: AquaStar "R" 12" models, Hayward, Waterway, American (Pentair #2 selling), PacFab with 1" deep existing frames and four screw hole pattern

Part # R12MFxxx

STANDARD COLORS

R12MF101 – White

R12MF102 – Black

R12MF103 – Light Gray


R12MF104 – Blue


R12MF105 - Dark Gray

R12MF108 - Tan

Replaces RFS12xxx

VGB 2008 Compliant





- 1. 12" square retrofit MoFlow suction outlet cover
- 2. 10 x 1-1/2" lg flat head Phillips Type A screw, 316 ss, qty 4
- 3. 10-24 x 1-1/4" lg flat head Phillips machine screw, 316 ss, qty 4
- 4. #10 x 1" lg flat head Phillips Type A screw, 316 ss, qty 4

 ${\bf P}$ 877-768-2717 ${\bf F}$ 877-276-POOL Outside the US: ${\bf P}$ +1-805-620-5060 ${\bf F}$ +1-949-336-1940 info@aquastarpoolproducts.com www.aquastarpoolproducts.com

