



SYSTEM:2 MOD MEDIA™

PLM SERIES ABOVEGROUND SYSTEMS

Greatest capacity for least maintenance.

The System:2 Mod Media system from Sta-Rite is the ultra-capacity filter ideally suited for aboveground pools. The Mod Media system handles dirt loads up to 15 times greater than sand filters of equivalent size. Balanced flow tank hydraulics direct water through each side of the filter module for uniform dirt loading. This prevents clogging and captures more dirt between cleanings to minimize maintenance time. You may go an entire season before you need to clean your PLM aboveground filter.

- You won't clean often, but it's easy when you do—just rinse in place with a garden hose.
- Quiet, highly efficient pump options keep operating costs low.
- Compact design fits easily in tight installations.



PENTAIR.COM

SYSTEM:2 MOD MEDIA™

Spray-and-go simplicity

The System:2 Mod Media System features a one-piece filter module that simply drops into the easily accessible tank. It's foolproof! When cleaning is necessary, just remove the lid (no tools are needed) and spray-rinse the module while it is still in place.* It only takes minutes to clean thoroughly and get back into service fast.

*Modules used in conjunction with certain pool/spa sanitizers may require soaking in special cleaning solutions.



CONVENIENCE AND VERSATILITY

The Mod Media Systems' small diameter footprint is the perfect fit for new and retrofit installations. Interchangeable ports provide multiple plumbing options, and the modular filter tank permits quick changing of filter media. Contemporary styling and matte black finish appear attractive in any pool setting.



The Mod Media System strips away particles as small as 20 microns (an average grain of beach sand is 100 to 2000 microns in diameter!).

KEY FEATURES

Top-mounted pressure gauge

Information panels are positioned for easy reading

Split-tank design

Permits rinse-in-place cleaning—super simple to achieve thorough cleaning fast

Posi-Ring® Closure

Easy to secure and lasts for years

System available with

Sta-Rite® OptiFlo® Series aboveground pumps

FILTER PERFORMANCE

Model	Pump (HP)	Filter Area (Sq. Ft.)	For Pools up to (Gal.) 8 Hr. Turnover
SRPLM1000E	1	100	48,000
SRPLM1000F	1.5	100	48,000
SRPLM1500E	1	150	72,000
SRPLM1500F	1.5	150	72,000

Operating Limits—Maximum continual operating pressure is 50 PSI. For pool/spa (bather) applications, the maximum operating water temperature within the filter is 104°F (40°C).

Note: Turnover capacity based on filter.



Simply Smarter.

TRADEGRADE

The TradeGrade family of products is exclusively made for and sold by the world's most demanding pool professionals.

1620 Hawkins Ave | Sanford, NC 27330 | United States | 800.831.7133 | staritepool.com

All indicated Pentair trademarks and logos are property of Pentair Inc. or its global affiliates in the U.S.A. and/or other countries. Third party registered and unregistered trademarks and logos are the property of their respective owners.