WELCOME TO thrml.

Thank you for choosing the AIRCAP™ from **thrml.**™ We sincerely appreciate your business and are excited to be a part of your hot tub experience.

We hope you enjoy the performance, efficiency, and convenience of your new AIRCAP™.

PLEASE REGISTER
YOUR PRODUCT

3 YEAR WARRANTY

thrml.

Unbox. Inflate. Zip.

AIRCAP

INSTALLATION GUIDE

UNBOX

Inside the box you will have the following items:

- AIRCAP™ cover
- 3 skirt sizes (3in, 6in, 9in)
- 2 way pump
- Orange container which holds a valve tightening tool, instructions
- 2 Patent Pending AIRLOC™ Wedges

INFLATE

1. Lay the AIRCAP™ on a clean, flat surface with the grey color/logo side facing up.
2. Remove the valve cap by twisting it off to expose the red valve.
3. Ensure the red valve is in the up position by pushing down on the spring and twisting until it rebounds upwards.
4. Attach the pump hose by twisting it clockwise until it locks securely into place. Be sure the hose is connected to the "Inflate" port on the pump. Inflate each chamber to 8 psi. Minimum 5 psi.
5. Once all chambers are inflated, remove the pump hose and securely screw the valve caps back on.
6. Place the AIRCAP™ on your hot tub with the **thrml.** logo positioned away/furthest from the side where you normally begin lifting the cover. This ensures the cover folds and operates as designed.

ZIP

Once the AIRCAP™ is installed on your hot tub, it's time to select the correct skirt size.

1. Determine the amount of the hot tub's acrylic shell that remains exposed below the cover.
2. Your AIRCAP™ includes three skirt length options. Choose the size that completely covers the exposed acrylic for the best appearance and insulation.
3. Each skirt length includes two skirt panels. Simply zip the two panels onto the AIRCAP™, wrapping them around your hot tub.

That's it—your AIRCAP™ installation is complete, and you're ready to enjoy the benefits of your new cover!

The AIRCAP™ includes (2) of our Patent Pending AIRLOC ™ Wedges, designed to help retain heat and improve your spa's energy efficiency. While they enhance performance, they are not required for the AIRCAP™ to function properly.

If you choose to use the wedges, attach one to each side of the cover using the pre-attached Velcro strips.

Important: Be sure to position the Velcro-fastened wedges on the section of the cover that is folded back second when opening the spa. This ensures the wedges remain securely attached and are not pulled off during normal use.

When closing the cover for the first few times, you may need to apply a small amount of pressure to seat the cover into the wedges. This is completely normal. As the cover settles in, it will naturally conform to the wedges, making the fit easier over time.

Thank you for being a valued member of the thrml.™ family.
We'd love to hear your feedback.

feedback@thrmltech.com

SET UP AND CARE INSTRUCTIONS:

