



1.5" NICHELESS LED POOL & SPA LIGHT



BRILLIANT LED POOL & SPA LIGHTING . . .



SIMPLE INSTALLATION & SERVICE

Installs in any 1.5" pool wall fitting and locks in place with a quarter-turn. Uses an industry-first quick disconnect IP68 connection for rapid service, winterizing or replacement.



HIGH PERFORMANCE. ENERGY EFFICIENT.

Precise engineering delivers a perfect balance of brightness, energy savings and longevity. Over 50,000 hours of low voltage LED life saves customers money and reduces service calls.



BUILT-IN CMP SMART SYNC™ TECHNOLOGY

Available with Smart Sync programming to synchronize with lighting and controls from major pool OEMs.



COMPLETELY SEAMLESS INSTALLATION

Other compact LED lights leave a visible fitting or trim around the light. The flush style fitting creates the most seamless 1.5" LED light installation, blending into the pool design.

The Brilliant Wonders ® 1.5" nicheless LED pool and spa light is versatile, easy to install and designed to sell. Create a sense of drama and excitement in any pool with bright LED light and colorful shows. Illuminate a pool, accent a spa or showcase steps, swim-outs and spillovers. Unleash your creativity with this designer LED light that is sized to fit in virtually any location. With so much to offer in one light, the next pool you build should be brilliant.

PRODUCT FEATURES

- Bright & Efficient Cree® LEDs Outlast and Outperform Other Lights
- RGBW LED Design for True White Performance
- Installs in Gunite, Fiberglass & Vinyl Pools
- Non-Metallic Design: No Bonding, No Grounding
- Heat-Conductive Body Increases LED & Electronics Life
- Soft Light Falloff: Smooth Blending, Soft Shadows, No Hard Edges
- Full Color, Full Stainless and Color Accent Stainless Faceplate Options
- Small Size can Retro-fit and Replace Almost Any Nicheless Light

. . . HIGH PERFORMANCE NICHELESS DESIGN



TECHNICAL GUIDE

- ETL Certified
- Available in 11 or 8 watt configurations
- Nicheless non-metallic design; no bonding; no grounding
- Standard model includes nine colors & five light shows
- 12V AC transformer required (not included)
- 140 degree beam angle
- Water-cooled with heat conductive PPS body
- 4" minimum water depth
- Wall or floor installation
- Clear gunite fitting with integrated waterstop
- Retrofit in most 1.5" wall fitting
- Durable, bayonet-style quarter turn installation
- 4.5" body with 6" watertight quick disconnect IP68 cord
- Synchronize with other popular pool OEM lighting systems









BRILLIANT WONDERS® 1.5" LED LIGHT ORDERING GUIDE

- Select light kit. Available
 in two cord lengths and two
 LED styles. Each kit includes
 LED light, flush fitting, water stop
 and multitool.
- **2. Smart Sync:** Order to match CMP or other OEM lighting.



20	WHITE WONDERS & A SHIELD HIGHT CARD (I C	T) // F	
BRILLIANT WONDERS® 1.5" LED LIGHT CMP/J-STYLE			
CMP P/N	DESCRIPTION	CORD LENGTH	WATTS
25503-568-109	11C RGBW COLOR FLUSH LIGHT KIT	100FT	11W
25503-568-159	11C RGBW COLOR FLUSH LIGHT KIT	150FT	11 W
25503-528-109	8C RGBW COLOR FLUSH LIGHT KIT	100FT	8 W
25503-528-159	8C RGBW COLOR FLUSH LIGHT KIT	150FT	8 W
BRILLIANT WONDERS® 1.5" LED LIGHT - P-STYLE			
25503-568-109P	11C RGBW COLOR FLUSH LIGHT KIT (P-STYLE)	100FT	11W
25503-568-159P	11C RGBW COLOR FLUSH LIGHT KIT (P-STYLE)	150FT	11 W
25503-528-109P	8C RGBW COLOR FLUSH LIGHT KIT (P-STYLE)	100FT	8 W
25503-528-159P	8C RGBW COLOR FLUSH LIGHT KIT (P-STYLE)	150FT	8 W
BRILLIANT WONDERS® 1.5" LED LIGHT - H-STYLE			
25503-568-109H	11C RGBW COLOR FLUSH LIGHT KIT (H-STYLE)	100FT	11W
25503-568-159H	11C RGBW COLOR FLUSH LIGHT KIT (H-STYLE)	150FT	11 W
25503-528-109H	8C RGBW COLOR FLUSH LIGHT KIT (H-STYLE)	100FT	8 W
25503-528-159H	8C RGBW COLOR FLUSH LIGHT KIT (H-STYLE)	150FT	8 W
BRILLIANT WONDERS® 1.5" LED LIGHT ACCESSORIES			
25503-519-300	CLEAR FLUSH LED LIGHT FITTING		
25503-510-300	WHITE FLUSH LED LIGHT FITTING		
25575-509-000	CLEAR WATER STOP ADAPTER		
25575-500-000	WHITE WATER STOP ADAPTER		

THE NEXT POOL YOU BUILD SHOULD BE BRILLIANT™

FOR OTHER BRILLIANT WONDERS® BRAND PRODUCTS VISIT C-M-P.COM/BRILLIANT

