



Procedures for Conditioning FilterBalls™ for First Time Use:



Hayward® Pro Series™ Side Mount - Sand Filter



Hayward® Pro Series™ Side Mount - Sand Filter

Directions for start-up (empty tank, system off):

- 1) Remove filter sand (if current vessel has sand in it).
- 2) Clean the sand particles that might be jammed in the lower underdrain laterals.
- 3) Add FilterBalls™ to tank (they are soft and can be pressed down when filling).
- 4) Replace control valve or tank lid and rinse the new media for 2 minutes, then backwash for 2 minutes.
- 5) Set to filter mode.
- 6) Backwash again when pressure increases by 5-7 PSI.

**VERY IMPORTANT INFORMATION,
PLEASE READ BEFORE PROCEEDING**

Not recommended for underdrains that use perforated cylinders



Recommended for use in underdrains that use laterals for effective use of filtration media

- 1) FilterBalls™ products (Green™, Blü™, Blü10™ or Sanž™) are for use in housings rated above 250 pounds of #20 filter sand
- 2) Minis should always be used when the media bed depth is 12" or less indepth. Generally these are sand vessels rated at 250 pounds or less.
- 3) FilterBalls Minis™ performance is not warranted in sand housings rated under 150 pounds of #20 filter sand. Please consult with a qualified pool technician for proper filter and pump system configurations for your pool.

