

HARDNESS PLUS

Adjuster

For Raising Calcium Hardness Levels in Pool Water

- Helps prevent damage to pool and equipment caused by soft water

Keep Out of Reach of Children
WARNING: HARMFUL IF SWALLOWED. EYE IRRITANT.
See First Aid and Carefully Read
Additional Precautions on Back Panel



Product Representation

LPM 14427 – Net Wt. 25 Lbs. (11.3 kg)

PRECAUTIONARY STATEMENTS

WARNING: Avoid contact with eyes and skin. Do not swallow. Wear safety glasses with side shields (or goggles) and rubber gloves. Keep out of reach of children. Do not predissolve or add this product to a small amount of water as heat is generated. Do not mix with other chemicals. Contains: Calcium chloride.

FIRST AID

IF INHALED:

- If dust from the material is inhaled, remove the affected person immediately to fresh air.

IF ON SKIN:

- Brush away excess of dry material.
- Flush skin with water.
- Obtain medical attention if irritation persists.

IF IN EYES:

- Rinse cautiously with water for several minutes.
- Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists, get medical advice/attention.

IF SWALLOWED:

- Call a poison center/doctor if you feel unwell.
- Rinse mouth.

DIRECTIONS FOR USE

Read entire label and use in accordance with precautionary statements and directions.

Leslie's Hardness Plus is used to raise calcium hardness in swimming pool water. Low calcium hardness causes pool water to become corrosive which can result in etched plaster, corrosion of equipment and fixtures or may cause metallic stains. The ideal range for calcium hardness in pool water is 200 to 400 ppm (parts per million). The minimum calcium hardness is 150 ppm.

HOW TO USE:

Add **Leslie's Hardness Plus** directly to pool water with pump running by broadcasting or scattering it over the water's surface. Do not predissolve or add this product to a small amount of water as heat is generated. Do not add this product immediately before or after adding **Leslie's Soda Ash** or **Leslie's Alkalinity Up** as the water may become cloudy.

1. Test water for hardness.
2. Determine the ppm increase desired by subtracting the current hardness level from the ideal or minimum level.
3. Refer to the chart for proper dosage.
4. Do not add **Leslie's Hardness Plus** on the same day that **Leslie's Soda Ash** or **Leslie's Alkalinity Up** has been added.

Raising hardness with **Leslie's Hardness Plus**.

DESIRED INCREASE IN HARDNESS

Pool Capacity (gallons)	10 ppm	30 ppm	50 ppm	100 ppm	150 ppm
5,000	10 oz.	1¼ lbs.	3 lbs.	6¼ lbs.	9¼ lbs.
10,000	1¼ lbs.	3¾ lbs.	6¼ lbs.	12½ lbs.	18¾ lbs.
15,000	1¾ lbs.	5½ lbs.	9½ lbs.	18¾ lbs.	28¼ lbs.
20,000	2½ lbs.	7½ lbs.	12½ lbs.	25 lbs.	37½ lbs.
25,000	3¼ lbs.	9½ lbs.	15¾ lbs.	31¼ lbs.	47 lbs.
50,000	6¼ lbs.	18¾ lbs.	31¼ lbs.	62½ lbs.	93¾ lbs.

PACKAGED FOR:

Leslie's Poolmart, Inc.
2005 E. Indian School Rd.
Phoenix, AZ 85016
www.lesliespool.com

QUALITY & SATISFACTION
GUARANTEED

Rev. 05/18



WARNING: This product can expose you to Bromate (when used in aqueous formulations with a chemical oxidizer such as ozone) which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov