



SAFETY DATA SHEET

5/26/2018

SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product code: LC-100 Product name: Neutral Seal

Recommended use: Stone Sealer Restrictions on use or sale: Distributed by RS Technologies

Company Information: RS Technologies, LLC

1900 W Chandler Blvd.

Suite 15-349

Chandler, AZ 85224

Company phone: 480-237-9363 **Emergency phone:** 1-800-535-5053

SECTION 2: HAZARD IDENTIFICATION

GHS CLASSIFICATION: Eye Irritation – Not Classified

Skin Irritation – Not Classified Acute Toxicity – Not Classified

Respiratory Sensitization - Classification Not Possible

Skin Sensitization - Not Classified

GHS LABEL REQUIREMENTS: Symbol – None

Signal Word - None Hazard Statement(s) - None Precautionary Statement(s) - None

OTHER HAZARDS: Hazardous decomposition products including hydrogen fluoride and other toxic fluorinated

compounds may be formed at high temperatures and during combustion. Inhalation of these compounds may result in serious lung irritation. Excessive exposure could result in delayed pulmonary edema in some cases, and on very high exposure, damage to the liver

and kidneys.

SECTION 3: INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	Wt%
Proprietary	Trade Secret	1-6
Water	7732-18-5	74.5-94.5
Fluoroalkyl methacrylate copolymer	Trade Secret _	
Emulsifiers	Trade Secret -	30
Tripropylene glycol	24800-44-0	7.5

SECTION 4. FIRST AID MEASURES

INGESTION: Consult a physician immediately.

EYE CONTACT: Flush with large amounts of water for 10-15 minutes. Consult a physician if needed. SKIN CONTACT: Wash affected area with soap and water. Remove contaminated clothing and shoes.

INHALATION: Leave the contaminated area and seek fresh air. If breathing is difficult, contact a physician.

SECTION 5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Alcohol foam, CO₂, dry chemical or water spray

PROTECTIVE EQUIPMENT: Use NIOSH/MSHA approved SCBA and bunker gear. Evolution of acidic gases

may require complete wash down of protective clothing prior to removal.

HAZARDOUS COMBUSTION PRODUCTS: In case of fire or if processing at high temperatures, toxic gases including

hydrofluoric acid, perfluoroisobutylene, and carbonyl fluoride may be formed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Ensure cleanup is done only by trained personnel wearing appropriate personal protective equipment.

Ventilate area and cover with absorbent material.

Collect spilled material in a container and seal.

Spilled material is a slipping hazard.

SECTION 7. HANDLING & STORAGE

HANDLING

Follow safe industrial hygiene practices and wear proper protective equipment.

Use only in well ventilated areas.

Wash hands thoroughly after handling.

Wash clothing after use.

Avoid contact with skin or eyes.

Do not breathe vapor or spray.

Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

If smoking tobacco becomes contaminated by this material, exposure to toxic gases through inhalation can occur.

Therefore, do not smoke in the work areas and wash hands and face after handling in order to avoid transfer of material onto tobacco.

STORAGE

Store material at -5 °C (23 °F) to 30 °C (86 °F).

Keep away from heat, steam, sunlight, sparks and openflame.

Store containers tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS & PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE LIMITS: No exposure limits available for the product.

Excessive exposure to thermal degradation products could result in delayed pulmonary edema in some cases, and on very high exposure, damage to the liver and kidneys. These substances may include: perfluoroisobutylene (TLV = 0.01 ppm Ceiling), carbonyl fluoride (TLV = 2 ppm TWA, 5 ppm STEL), hydrogen

fluoride (TLV = 2 ppm Ceiling, 0.5 ppm TWA).

RESPIRATORY PROTECTION: Use respirator suitable for protection when spraying this material. If material is

heated above 200 °C, use a positive pressure air supplied respirator or SCBA.

EYE PROTECTION: Safety glasses with side shields or goggles

PROTECTIVE CLOTHING: Chemical resistant gloves and protective clothing should be worn when handling

this material.

VENTILATION: Use local exhaust ventilation if material is heated above 200 °C.

OTHER PROTECTIVE EQUIPMENT: Eyewash station and safety shower.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE: Off white liquid
ODOR: Slight sweetish odor
ODOR THRESHOLD: Not Available
pH: 2.0 - 5.0

MELTING POINT:

Not Applicable

FREEZING POINT:

Approximately 0 °C

BOILING POINT/RANGE: Approximately 100 °C (water)

FLASH POINT: > 200 °F (Closed Cup), > 209 °F (Open Cup)

FLAMMABLE LIMITS: LEL – Not Available

UEL - Not Available

EVAPORATION RATE (Butyl acetate=1): Not Available VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available

SPECIFIC GRAVITY (H₂O=1): Approximately 1.1 at 25 °C

SECTION 10. STABILITY & REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat, sparks, and open flame

INCOMPATIBILITIES: May react with metals, such as sodium, magnesium, aluminum at elevated

temperatures (above 425 $^{\circ}\text{C});$ may react upon prolonged exposure to fluorine or in

oxygen-fluorine mixtures at high temperatures and pressures. Contact with

incompatible materials may result in fire or explosion.

HAZARDOUS POLYMERIZATION: Should not occur

HAZARDOUS DECOMPOSITION: Decomposition or by-products and toxic by-products including hydrofluoric acid,

perfluoroisobutylene, and carbonyl fluoride may be formed at very high temperatures.

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS OF EXPOSURE

Ingestion: May be harmful if swallowed
Eye Contact: May cause mild irritation
Skin Contact: May cause skin irritation

Inhalation: May cause respiratory irritation

CHRONIC EFFECTS OF EXPOSURE: No Data Available

ACUTE TOXICITY: LD50: Oral, rat >2,000 mg/kg

SKIN CORROSION/IRRITATION: Skin Irritation by Draize (rabbit): Non-irritating

SERIOUS EYE DAMAGE/IRRITATION: Eye Irritation by Kay and Calandra (rabbit): Mildly irritating

RESPIRATORY OR SKINSENSITIZATION: Skin by Local Lymph Node Assay (mouse): Negative

GERM CELL MUTAGENICITY: No Data Available

CARCINOGENICITY: None of the components in this material are listed by NTP, OSHA or IARC.

REPRODUCTIVE TOXICITY:

STOT-SINGLE EXPOSURE:

STOT-REPEATED EXPOSURE:

ASPIRATION HAZARD:

No Data Available

No Data Available

Not Applicable

SECTION 12. ECOLOGICAL INFORMATION

BIODEGRADABILITY: No data
BIOACCUMULATION: No data

SECTION 13. DISPOSAL CONSIDERATIONS

Comply with Federal, State and Local regulations concerning health and environment when disposing of materials. Regulations may also apply to empty containers, liners, or rinsate. DO NOT INCINERATE unless incinerator is capable of scrubbing hydrogen fluoride and other acidic combustion products.

SECTION 14. TRANSPORT INFORMATION

UN CLASSIFICATION: Not applicable DOT HAZARD DESCRIPTION: Not applicable

CANADIAN TRANSPORTATION OF

DANGEROUS GOODS (TDG): Not applicable

SECTION 15. REGULATORY INFORMATION

TSCA: All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic

Substance Control Act (TSCA) Chemical Substance Inventory.

The base polymer is subject to a consent order regarding a premanufacturing notice under Section 5(e) of

TSCA. In addition, the base polymer is subject to export notification under Section 12(b) of TSCA.

Other: State and local regulations may have specific requirements for this product or components of this product;

consult specific state and local regulatory requirements for additional information.

SECTION 16. OTHER INFORMATION

We believe the information contained herein is accurate and current as of the date of this Safety Data Sheet. Nevertheless, the user must evaluate and determine whether the conditions for use and application of the product, including proper disposal thereof, are appropriate, safe and legal.

SDS Issued: 05/26/2015