Product Name: Gunite Catalyst Product Code: A7725 Catalyst

Date issued: 8/31/2015

SECTION 1: IDENTIFICATION

Product Name

Gunite Catalyst

Product Code #

A7725 Catalyst

Identified Uses

Protective Coating

Manufacturer: Kelley Technical Coatings 1445 South 15th Street

P.O. Box 3726

Louisville, Kentucky 40201-3726

Emergency Contact Number:

Night: 800-424-9300

Information Telephone Number: 502-636-2561

SECTION 2: HAZARDS IDENTIFICATION

Flammable Liquid 3 Aspiration Hazard 1 Skin Corrosion 1A-1C Skin Sensitization 1 Acute Toxicity - Inhalation 4

Carcinogenicity 2

Specific Target Organ Toxicity (Single Exposure) 3

Day: 502-636-2561

GHS Classification

GHS Label Elements

Hazard Symbols



Signal Word

Danger

Hazard Statements

H226 Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction

H332 Harmful if inhaled

H351 Suspected of causing cancer

H336 May cause drowsiness or dizziness

Precautionary statements

Prevention

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No Smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapor/spray.

P271 Use only outdoors or in well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear PPE to protect skin/eyes.

P281 Use personal protective equipment as required.

Response

P312 Call a poison center or doctor if you feel unwell.

P363 Wash contaminated clothing and wash before reuse.

Product Name: Gunite Catalyst Product Code: A7725 Catalyst

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P370 + P378 In case of fire: Use ABC Dry Chemical for extinction.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

Date issued: 8/31/2015

rinsing.

Storage/ Disposal

P405 Store locked up.

P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.

P403 + P233 Store in well ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

Other Hazards

OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

SECTION 3 : COMPOSITION INFORMATION

Chemical Designation	CAS No.	% by Weight
magnesium silicate	14807-96-6	40 - 50%
polyamide resin	68410-23-1	30 - 40%
light aromatic naphtha	64742-95-6	10 - 20%
1,2,4 trimethylbenzene	95-63-6	5 - 10%
triethylenetetramine	112-24-3	1 - 5%
rheological additive	unknown	1 - 5%
cumene	98-82-8	0.1 - 1%

SECTION 4: FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance

Eyes:

Flush with plenty of cool water for at least15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get

immediate medical attention.

Skin: Inhalation: Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention. Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.

Ingestion:

Do not induce vomiting - seek immediate medical attention.

Notes to Physician

Treat symptomatically

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific Hazards

arising from the

Chemical Special protective Closed containers may rupture if exposed to fire or extreme heat.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective

Equipment:

gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

cannot be contained.

Methods for Clean-up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface

thoroughly.

Product Name: Gunite Catalyst Product Code: A7725 Catalyst

725 Catalyst ____ Date issued: 8/31/2015

Other Information

None known

SECTION 7: HANDLING & STORAGE

Handling:

Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge,

all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

Storage:

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2*21

HMIS CODE: 4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD, * - Chronic Hazard Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

Exposure Limits

Hazardous Components OSHA PEL ACGIH TLV magnesium silicate 20 mppcf 2 mg/m3 (R) polyamide resin NE NE light aromatic naphtha NE NE 1,2,4 trimethylbenzene 25 ppm 25 ppm triethylenetetramine 100 ppm NE rheological additive 5 mg/m3 (R) 3 mg/m3 (R)cumene 50 ppm 50 ppm

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit (R) = Respirable fraction

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective

Equipment

Eyes/Face:

Safety goggles or full face shield

Skin:

Protective gloves and impervious clothing.

Respiratory Protection:

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH

approved respirator specified for paint spray or organic vapors.

Hygiene Practices:

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after

handling. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: liquid Odor: Solvent odor Odor threshold: Not determined VOC lb/gal 1.92 VOC (g/L) 230.10 VOC (lb/gal) less exempt 1.92 VOC (g/L) less exempt 230.10 Relative Density (LB/GAL): 11.20 Specific Gravity (g/L): 1.34 Flash Point (F): 110.00 Flammability: Not determined Upper/lower flammability limits: Not available Auto-ignition temperature: Not determined Decomposition temperature: Not determined Evaporation rate: Not available Vapor Pressure (mmHg): Not available Vapor Density: Not available Initial Boiling Point (F): Not available Boiling Point Range (F): Not available Freezing Point (F): Not determined Melting Point (F): Not determined pH Not available Viscosity Not available Solubility (ies): Not determined Partition coefficient: n-Not determined

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:

octanol/water

Stable under normal conditions. Hazardous polymerization does not occur.

Product Name: Gunite Catalyst Product Code: A7725 Catalyst

Keep away from open flames, hot surfaces, static electricity and sources of ignition.

Conditions to Avoid: Incompatible with strong acids and bases and strong oxidizing agents.

Materials to Avoid: Thermal decomposition can lead to release of irritating gases and vapors. Hazardous Decomposition Products:

None under normal conditions of use. Possibility of Hazardous Reactions:

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity			
Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
magnesium silicate	NA	NA	NA
polyamide resin	NA	NA	NA
light aromatic naphtha	8,400	NA	NA
1,2,4 trimethylbenzene	5,000	18,000	NA
triethylenetetramine	2,500	805	NA
rheological additive	NE	NE	NE
cumene	NA	NA	NA

Chronic Toxicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Component

IARC

NTP

OSHA

Date issued: 8/31/2015

cumene

2B - Possible Human Carcinogen

Not listed

Listed

SECTION 12: ECOLOGICAL INFORMATION

No ecological information available

SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

SECTION 14: TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

SECTION 15: REGULATORY INFORMATION

US TSCA:

Yes - All components are listed or exempt

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard	YES
Chronic Health Hazard	YES
Fire Hazard	NO
Sudden Release of Pressure Hazard	NO
Reactive Hazard	NO

SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation

Cas No.

Weight %

Product Name: Gunite Catalyst Product Code: A7725 Catalyst

Date issued: 8/31/2015

1,2,4 trimethylbenzene

95-63-6

5 - 10%

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

Chemical Designation

Cas No.

Weight %

cumene

98-82-8

0.1 - 1%

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

Date issued: 8/31/2015

VER 01

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.