2009 SPA CONTROL CATALOG







About us:

Hydro-Quip... the Smart Choice

Hydro-Quip has been providing innovative, dependable and high quality portable spa and hot tub controls to the industry since 1982. Hydro-Quip continues to offer the broadest selection of controls to fit every spa or hot tub and we continue to lead the industry in innovation and "down to earth" product features by designing products that address the real needs and desires of today's portable spa and hot tub buyers.

"down to earth" features such as this long list of industry firsts:

<u>System Mis-Wire Protection</u> Protection from improper electrical installations

<u>Universal Circuit Voltages</u> Flexible circuit designs accept 120V or 240V

Universal Retro-Fit Systems Complete ready to install Control Kits

<u>Versi-Heat Remote Heaters</u> Remote heater for added convenience

Slide Heater Control Systems Movable heater provides maximum flexibility

<u>Visual Diagnostic System</u> Provides easy system diagnostics

<u>Built-in Ground Fault Protection</u> Economical GFCI safety protection

In addition to our innovative spa and hot tub products, you will find our customer service personnel to be unmatched in their first hand product knowledge. Our customer service, sales and technical support people are all industry veterans that understand not only our product but the applications that our customers encounter on a daily basis. We take great pride in our reputation for superior quality and responsive customer service all at a competitive price.

In the following pages you will find our family of products which address your engineering and marketing requirements, production concerns and aftermarket needs. Please contact us directly if you have any additional needs or requirements.

TABLE OF CONTENTS

| TABLE OF CONTENTS | 1 |
|-------------------------------|----|
| CS500 AIR | 2 |
| CS700 AIR | 3 |
| CS4000 AIR SLIDE | 4 |
| CS6000 AIR SLIDE | 5 |
| CS6000 AIR VERSI-HEAT | 6 |
| CS4000 SOLID STATE SLIDE | 7 |
| CS6000 SOLID STATE SLIDE | 8 |
| CS6000 SOLID STATE VERSI-HEAT | 9 |
| CS7000 SOLID STATE SLIDE | 10 |
| CS9700 SOLID STATE SLIDE | 11 |
| CS9700 SOLID STATE VERSI-HEAT | 12 |
| CS8000 OUTDOOR SOLID STATE | 13 |
| ES4000 AIR | 14 |
| ES6000 AIR | 15 |
| ES4000 SOLID STATE | 16 |
| ES6000 SOLID STATE | 17 |
| ES9700 SOLID STATE | 18 |
| ES8000 OUTDOOR SOLID STATE | 19 |
| HEATMAX RHS | 20 |
| SILENT AIRE BLOWER | 21 |
| UNIVERSAL RITE FIT HEATER | 22 |
| HYDROQUIP LIMITED WARRANTY | 23 |
| WARRANTY PROCEDURE | 24 |



Standard:

- 1.125/4.5KW Heater in ABS Housing
 24hr Timer with Mode Switch("T" units)
- 24nr Timer with Mode Switch("1"
 Full Range Thermostat
- Full Range Thermostat
 Ozone circuit (120V/240V)
- Light Circuit (120V)
- 15A GFCI Cord End (120V models only)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- "Paint-Lock" rust proof electrical enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

12V Light Kit (HQ Pt# 37-0029-SM)

CS500 Series Air Control System

Compact - Classic - Convenient: Three words that come to mind when describing the satisfaction of installing and/or owning a CS500 series control from Hydro-Quip. From the classic electromechanical reliability of the components to the corrosion-proof ABS heater housing. No other manufacturer provides the same level of time and money saving features.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL WILL OPERATE 1 PUMP & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| MODEL | CS500-A | CS500-C | CS500T-A | CS500T-C | CS500T-C9 |
|-------------|---------|---------|----------|----------|-----------|
| VOLTAGE | 120V | 240V | 120V | 240V | 240V |
| PUMP1(2SPD) | 120V | 120V | 120V | 120V | 240V |
| BLWR | 120V | 120V | 120V | 120V | 120V |
| OZONE | YES | YES | YES | YES | YES |
| GFCI | 15A | NA | 15A | NA | NA |

"T" = INCLUDES A 24 HOUR TIME CLOCK FOR FILTRATION

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| 011(0011(0) | WAXIMOW AIM O | |
|------------------|---------------|--|
| PUMP | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 120V LIGHT | 1A | |
| HEATER | 18.75A | |

MAYIMI IM AMPS

INSTALLATION KIT (Included)



Kit Includes:

- Pump, Blower & Ozone Cords
- Air Transmitters
- Air Tubing
- · Tailpieces w/Gaskets

SYSTEM DIMENSIONS:

14"W X 6"H X 6"D

Shipping Weight:

12 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (16, 32, 64, 128+)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





Standard:

- 1.125/4.5KW Heater Assembly
- 24hr Timer with Mode Switch("T" units)
- **Full Range Thermostat**
- Ozone circuit (120V/240V)
- Light Circuit (120V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- Standard Smart Cords
- "Paint-Lock" rust proof enclosure Heater "ON" Indicator Light
- **Detailed Owners Manual**
- **Detailed Wiring Diagram**

Available Options:

- Custom Faceplate Silk Screening
- Custom keypad labels available
- 12V Light Kit (HQ PT# 37-0029-SM)

CS700 Series **Air Control System**

Compact - Classic - Convenient: Three words that come to mind when describing the satisfaction of installing and/or owning a CS700 series control from Hydro-Quip. From the classic electromechanical reliability of the components no other manufacturer provides the same level of time and money saving features.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL WILL OPERATE 1 PUMP & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| MODEL | CS700-A | CS700-C | CS700-D | CS700-E | CS700T-A | CS700T-C |
|------------|---------|---------|---------|---------|----------|----------|
| HEATER kW | 1.5 | 1.5 | 1.0 | 2.0 | 1.5 | 4.5 |
| VOLTAGE | 120V | 120V | 120V | 240V | 120V | 240V |
| PUMP1(2SPD |) 120V | 120V | 120V | 120V | 120V | 120V |
| BLWR | NA | NA | NA | 120V | NA | 120V |
| OZONE | YES | YES | YES | YES | YES | YES |
| GFCI | N/A | 20A | 15A | N/A | 20A | N/A |

"T" = INCLUDES A 24 HOUR TIME CLOCK FOR FILTRATION

ELECTRICAL INPUT SPECIFICATION:

| SINGLE PHASE |
|--------------|
| 120/240VAC |
| 50/60HZ |

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12 LIGHT | 1A | |
| HEATER | 18.75A | |

INSTALLATION KIT (Included)



Kit Includes:

- Pump, Blower & Ozone Cords
- **Air Transmitters**
- Air Tubing
- Tailpieces w/Gaskets

SYSTEM DIMENSIONS:

13"W X 9.5"H X 4"D

Shipping Weight:


13.5 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (16, 32, 64, 128+) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS



Standard:

- 1.375/5.5KW "SLIDE" Heater Assembly
- 24hr Timer with Mode Switch
- Full Range Thermostat
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- "VDS" Visual Diagnostics
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

CS4000 *SLIDE* Series Air Control System

The CS4000 *SLIDE* series control system offers our New "L" shaped heater that allows direct mounting above the pump. Incorporating the *SLIDE* feature, makes this unit perfect for all retro-fit applications!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL WILL OPERATE UP TO 2 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS4009-US1 | CS4009-US2 |
|-----------|------------|------------|
| PUMP 1 | 2 SPD | 2 SPD |
| PUMP 2 | N/A | 1 SPD |
| BLOWER | YES | YES |
| OZONE | YES | YES |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------|--------------|--|
| PUMP (S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |

INSTALLATION KIT (Included)



Kit Includes:

- · Pump, Blower & Ozone Cords
- · Air Transmitters
- Air Tubing
- Tailpieces w/Gaskets

SYSTEM DIMENSIONS:

17"W x 9.5"H x 6"D

SHIPPING WEIGHT:

15 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (16, 32, 64, 128+)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

CONTROLLER OPTIONS







3 & 4 Button Digital Spaside Controller HQ PT# 34-0037D-S (4 button) 34-0039D-S (3 button)

All Hydro-Quip Aire control systems are spaside controller ready.



Standard:

- 1.375/5.5KW "SLIDE" Heater Assembly
- 24hr Timer with Mode Switch
- Full Range Thermostat
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- "VDS" Visual Diagnostics
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

CS6000 *SLIDE* Series Air Control System

The Hydro-Quip CS6000 *SLIDE* series control is our most versatile Electro-Mechanical unit we have to offer. It's the only unit of its kind with a vertically adjustable heater that can also be removed and installed remotely. That makes this series the perfect "all in one" unit for many retro-fit applications!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL WILL OPERATE UP TO 2 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS6009-US1 | CS6009-US2 |
|-----------|------------|------------|
| PUMP 1 | 2 SPD | 2 SPD |
| PUMP 2 | N/A | 1 SPD |
| BLOWER | YES | YES |
| OZONE | YES | YES |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

| SINGLE PHASE |
|--------------|
| 120/240VAC |
| E0/00117 |

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------|--------------|--|
| PUMP (S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |

INSTALLATION KIT (Included)



Kit Includes:

- · Pump, Blower & Ozone Cords
- Air Transmitters
- Air Tubing
- · Tailpieces w/Gaskets

SYSTEM DIMENSIONS:

15"W x 11"H x 6"D

SHIPPING WEIGHT:

18 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC) INDIVIDUAL (CUSTOM) CELL/BULK PACK (12, 24, 48, 96) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

CONTROLLER OPTIONS







3 & 4 Button Digital Spaside Controller HQ PT# 34-0037D-S (4 button) 34-0039D-S (3 button)

All Hydro-Quip Aire control systems are spaside controller ready.





Standard:

- 1.375/5.5KW VERSI-HEAT Assembly
- 24hr Timer with Mode Switch
- **Full Range Thermostat**
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- "VDS" Visual Diagnostics
- **Lighted Smart Cords**
- "Paint-Lock" rust proof enclosure Heater "ON" Indicator Light
- **Detailed Owners Manual**
- **Detailed Wiring Diagram**

Available Options:

- **High Current GFCI**
- Custom Faceplate Silk Screening
- Custom keypad labels available

CS6000 VERSI-HEAT Series **Air Control System**

The Hydro-Quip solid-state CS6000 series controls represents the finest in classic Electro Mechanical dependabilty. The durabilty of the components used in mechanical controls is legendary and Hydro-Quip bares no expense at equipping our controls with the best available.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

> THIS CONTROL WILL OPERATE UP TO 2 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS6008-U1 | CS6008-U2 | |
|-------------|-----------|-----------|--|
| PUMP 1 | 2 SPD | 2 SPD | |
| PUMP 2/BLWR | N/A | 1 SPD | |
| BLOWER | 1 SPD | 1 SPD | |
| OZONE | YES | YES | |
| 12V LIGHT | YES | YES | |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP (S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12 LIGHT | 1A | |
| HEATER | 23∆ | |

INSTALLATION KIT (Included)



Kit Includes:

- Pump, Blower & Ozone Cords
- **Air Transmitters**
- Air Tubing
- Tailpieces w/Gaskets

SYSTEM DIMENSIONS:

15"W x 11"H x 3"D

Shipping Weight:

20 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC) INDIVIDUAL (CUSTOM) CELL/BULK PACK (16, 32, 64, 128+) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

CONTROLLER OPTIONS





HQ PT# 34-0037A-S (4 button) 34-0039A-S (3button)



4 Button Digital **Spaside Controller** HQ PT# 34-0037D-S (4 button) 34-0039D-S (3 button)

All Hydro-Quip Aire control systems are spaside controller ready.





Standard:

- 1.375/5.5KW "SLIDE" Heater Assembly
 - Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- Smart-Freeze Protection
- "VDS" Visual Diagnostics
- Lighted Smart Cords
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

INSTALLATION KIT (Included)



Kit Includes:

- Spaside Control
- Pump, Blower & Ozone Cords
- · Thermo-well Housing
- Tailpieces w/Gaskets
- · Spaside Adapter Plate

KEYPAD OPTIONS







ECO-5 Keypad (CS4109) HQ PT#: 34-0207 ECO-3 Keypad (CS4239, CS4339)

ECO-6 Keypad (CS4209, CS4229)

All Hydro-Quip control systems include a keypad by default. If a different keypad is desired options may be available, please contact your Hydro-Quip representative for more details.

CS4000 *SLIDE* Series Solid State Control System

The CS4000 SLIDE series control system offers our New "L" shaped heater that allows direct mounting above the pump. Incorporating the SLIDE feature, makes this unit perfect for all retro-fit applications!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL WILL OPERATE UP TO 3 PUMPS OR 2 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS4109-US | CS4209-US | CS4229-US | CS4239-US | CS4339-US |
|------------------------------|------------|-----------|-----------|-----------|-----------|
| PUMP 1 | 1 OR 2 SPD | 2 SPD | 2 SPD | 2 SPD | 2 SPD |
| PUMP 2/BLWR | NA | 1 SPD | 2 SPD | 1 SPD | 2 SPD |
| PUMP 3/BLWR | NA | NA | NA | 1 SPD | 1 SPD |
| OZONE | YES | YES | YES | YES | YES |
| CIRC PUMP | NA | YES | NA | YES | YES |
| 12V LIGHT | YES | YES | YES | YES | YES |
| Export models also available | | | | | |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12V LIGHT | 1A | |
| HEATER | 23A | |

SYSTEM DIMENSIONS:

17"W x 9.5"H x 6"D

SHIPPING WEIGHT:

10 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (16, 32, 64, 128+)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





Standard:

- 1.325/5.5KW "SLIDE" Heater Assembly
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- Smart-Freeze Protection
- "VDS" Visual Diagnostics
- **Lighted Smart Cords**
- Heater "ON" Indicator Light
- **Detailed Owners Manual**
- **Detailed Wiring Diagram**

Available Options:

- **High Current GFCI**
- Custom Faceplate Silk Screening
- Custom keypad labels available

INSTALLATION KIT (Included)



Kit Includes:

- **Spaside Control**
- Pump, Blower & Ozone Cords
- Thermo-well Housing
- Tailpieces w/Gaskets
- **Spaside Adapter Plate**

KEYPAD OPTIONS



(CS6109)



HQ PT#: 34-0197



ECO-6 Keypad ECO-3 Keypad (CS6239, CS6339) (CS6209, CS6229)

All Hydro-Quip control systems include a keypad by default. If a different keypad is desired options may be available, please contact your Hydro-Quip representative for more details.

CS6000 SLIDE Series Solid State Control System

The CS6000 SLIDE Series Control systems were designed for the spa and service professional. Mount the heater where you need it - anywhere along the back of the control box, underneath, or remote! You can offer the maximum range of controls while stocking a minimum number of different components!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

> THIS CONTROL SYSTEM WILL OPERATE UP TO 3 PUMPS OR 2 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS6109-US | CS6209-US | CS6229-US | CS6239-US | CS6339-US |
|---------------|---------------|-----------|-----------|-----------|-----------|
| PUMP 1 | 1 OR 2 SPD | 2 SPD | 2 SPD | 2 SPD | 2 SPD |
| PUMP 2/BLWR | NA | 1 SPD | 2 SPD | 1 SPD | 2 SPD |
| PUMP 3/BLWR | NA | NA | NA | 1 SPD | 1 SPD |
| OZONE | YES | YES | YES | YES | YES |
| CIRC PUMP | NA | YES | NA | YES | YES |
| 12V LIGHT | YES | YES | YES | YES | YES |
| Export models | also availabl | e | | | |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12V LIGHT | 1A | |
| HEATER | 23A | |

SYSTEM DIMENSIONS:

15"W x 11"H x 6"D

SHIPPING WEIGHT:

19LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC) INDIVIDUAL (CUSTOM) CELL/BULK PACK (12, 24, 48, 96) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





Standard:

- 1.375/5.5KW VERSI-HEAT Assembly
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- Smart-Freeze Protection
- "VDS" Visual Diagnostics
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

INSTALLATION KIT (Included)



Kit Includes:

- Spaside Control
- Pump, Blower & Ozone Cords
- · Thermo-well Housing
- Tailpieces w/Gaskets
- Spaside Adapter Plate

KEYPAD OPTIONS



(CS6108)







ECO-6 Keypad (CS6208, CS6228) HQ PT#: 34-0208

All Hydro-Quip control systems include a keypad by default. If a different keypad is desired options may be available, please contact your Hydro-Quip representative for more details.

CS6000 Series *VERSI-HEAT*Solid State Control System

The Hydro-Quip solid-state CS6000 series controls represents the finest entry to mid level control system on the market today. No other manufacture provides the same level of time and money saving features.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL SYSTEM WILL OPERATE UP TO 2 PUMPS OR 1 PUMP & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS6108 | CS6208 | CS6228 | CS6238 | CS6338 |
|-------------|------------|--------|--------|--------|--------|
| PUMP 1 | 1 OR 2 SPD | 2 SPD | 2 SPD | 2 SPD | 2 SPD |
| PUMP 2/BLWR | NA | 1 SPD | 2 SPD | 1 SPD | 2 SPD |
| PUMP 3/BLWR | NA | NA | NA | 1 SPD | 1 SPD |
| OZONE | YES | YES | YES | YES | YES |
| CIRC PUMP | NA | YES | NA | YES | YES |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12 LIGHT | 1A | |
| HEATER | 23∆ | |

SYSTEM DIMENSIONS:

15"W x 11"H x 3"D

SHIPPING WEIGHT:

19 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (16, 32, 64, 128+)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





NEW HEATER "SLIDE" FEATURE!

HEATER SLIDES FROM TOP TO BOTTOM!

FEATURES & OPTIONS

Standard:

- 1.375/5.5KW "SLIDE" Heater Assembly
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- Smart-Freeze Protection
- Brushed Aluminum Enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- Custom Faceplate Silk Screening
- Custom keypad labels available

INSTALLATION KIT (Included)



Kit Includes:

- Spaside Control
- Pump, Blower & Ozone Cords
- · Thermo-well Housing
- Tailpieces w/Gaskets
- · Spaside Adapter Plate

KEYPAD OPTIONS



ECO-1 Keypad (CS7109) HQ PT#: 34-0193 Standard



ECO-2 Keypad (CS7509) HQ PT#: 34-0200

All Hydro-Quip control systems include a keypad by default. If a different keypad is desired options may be available, please contact your Hydro-Quip representative for more details.

CS7000 SLIDE Series Solid State Control System

The CS7000 SLIDE series control system is the smallest of our SLIDE series units and replaces many of the compact units on the market today. Built with the spa and service professional in mind, this unit offers basic features in a compact control box, making it one of our most economical of the series.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL SYSTEM WILL OPERATE UP TO 2 PUMPS OR 1 PUMP & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS7109-US | CS7509-US |
|--------------------|------------|------------|
| PUMP 1 | 1 OR 2 SPD | 1 OR 2 SPD |
| PUMP 2/BLWR | N/A | 1 SPD |
| OZONE | YES | YES |
| CIRC PUMP | N/A | YES |
| 12V LIGHT | YES | YES |
| Export models also | available | |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12V LIGHT | 1A | |
| HEATER | 23A | |

SYSTEM DIMENSIONS:

15"W x 10"H x 6"D

SHIPPING WEIGHT:

12 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (12, 24, 48, 96)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





NEW HEATER "SLIDE" FEATURE!

SLIDES from top to bottom!

FEATURES & OPTIONS

Standard:

- 1.375/5.5KW "SLIDE" Heater Assembly
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- SMART-ECON Economy mode settings
- SMART-FREEZE Protection
- "VDS" Visual Diagnostics
- Lighted SMART Cords
- "Paint-Lock" rust proof enclosure Heater "ON" Indicator Light
- Detailed Owners Manual
- **Detailed Wiring Diagram**

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available In-House Full Function Keypad (up to 200 ft.)
- IR Remote Control
- Auxiliary Keypad

INSTALLATION KIT (Included)



Kit Includes:

- **Spaside Control**
- Pump, Blower & Ozone Cords
- Thermo-well Housing
- Tailpieces w/Gaskets
- **Spaside Adapter Plate**

KEYPAD OPTIONS











HTII 10 Button Keypad (Included) HQ PT#: 34-0190A



CS9700 SLIDE Series Solid State Control System

The CS9700 SLIDE series control system is simply the most advanced spa control system available today. With features that provide extreme performance and maximum efficiency, this unit is by far the best the system we have to offer!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL SYSTEM WILL OPERATE UP TO 3 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS9709-US |
|----------------|------------|
| PUMP 1 | 1 or 2 SPD |
| PUMP 2 | 1 or 2 SPD |
| PUMP 3 | 1 SPD |
| AUX CIRCUIT(S) | 2 |
| BLOWER | 1-3 SPD |
| OZONE | YES |
| CIRC PUMP | YES |
| 12V LIGHT | 1-3 STEP |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE (DOMESTIC MODEL) 1, 2 OR 3 PHASE (EXPORT CE MODEL)

120/240VAC 50/60HZ

CIPCLIIT(S)

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCOTT(S) | MAXIMOM AMI 3 | |
|------------------|---------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12V LIGHT | 1A | |
| HEATER | 23A | |
| AUXII IARY | 5A | |

MAYIMIIM AMPS

SYSTEM DIMENSIONS:

15"W x 12"H x 6"D

SHIPPING WEIGHT:

19 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC) INDIVIDUAL (CUSTOM) CELL/BULK PACK (16, 32, 64, 128+) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





Standard:

- 1.375/5.5KW VERSI-HEAT Assembly
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty
- Installation Kit (see below)

Exclusive:

- Smart-Freeze Protection
- "VDS" Visual Diagnostics
- **Lighted Smart Cords**
- "Paint-Lock" rust proof enclosure Heater "ON" Indicator Light
- **Detailed Owners Manual Detailed Wiring Diagram**

Available Options:

- **High Current GFCI**
- Custom Faceplate Silk Screening
- Custom keypad labels available
- In-House Full Function Keypad (up to 200')
- IR Remote Control
- Auxiliary Keypad

INSTALLATION KIT (Included)



Kit Includes:

- **Spaside Control**
- Pump, Blower & Ozone Cords
- Thermo-well Housing
- Tailpieces w/Gaskets
- **Spaside Adapter Plate**

KEYPAD OPTIONS











HTII 10 Button Keypad (Included) HQ PT#: 34-0190A



CS9700 Series VERSI-HEAT **Solid-State Control System**

The Hydro-Quip solid-state CS9700 series control...Simply the most advanced spa control system available today. With features that provide extreme performance and maximum efficiency, the user is in total of the spa control indoors or out. No other manufacture provides the same level of time and money saving features.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

> THIS CONTROL SYSTEM WILL OPERATE UP TO 3 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS9708-U |
|----------------|------------|
| PUMP 1 | 1 or 2 SPD |
| PUMP 2 | 1 or 2 SPD |
| PUMP 3 | 1 SPD |
| AUX CIRCUIT(S) | 2 |
| BLOWER | 1-3 SPD |
| OZONE | YES** |
| CIRC PUMP | YES** |
| 12V LIGHT | 1-3 STEP |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE (DOMESTIC MODEL) 1, 2 OR 3 PHASE (EXPORT CE MODEL)

120/240VAC 50/60HZ

CIPCLIIT(S)

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(3) | WAXIMOW AWIF 3 | |
|------------------|----------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |
| AUXII IARY | 5A | |

MAYIMIIM AMDS

SYSTEM DIMENSIONS:

15"W x11"H x 3"D

SHIPPING WEIGHT:

23 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC) INDIVIDUAL (CUSTOM) CELL/BULK PACK (16, 32, 64, 128+) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





Standard:

- Outdoor Weathertight Construction
- 5.5/11KW Heater Assembly
- Electric or Gas ready
- Ozone circuit (120V/240V)
- Light Circuit (120V/12V)
- Wall Mount Brackets
- Installation Kit (see below)

Exclusive:

- Smart-Freeze Protection
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Pressure and Flow Switch Protected
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- Foot Bracket (Shown)
- Custom Faceplate Silk Screening
- Custom Keypad Labels Available
- In-House Full Function Keypad (up to 200')
- IR Remote Control
 Auxiliary Keypad
 -

INSTALLATION KIT (Included)



Kit Includes:

- Spaside Control w/ 25' Cord
- Pump, Blower & Ozone Cords
- Thermo-well Housing
- Tailpieces w/Gaskets
- Spaside Adapter Plate

KEYPAD OPTIONS









HTII 10 Button Keypad (Included) HQ PT#: 34-0190A



CS8000 Outdoor Series Solid State Control System

The Hydro-Quip solid-state CS8000 series controls represent the finest in outdoor systems on the market today. No other manufacturer's outdoor control systems offer such an extensive array of available options or provides the same level of time and money saving features.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

THIS CONTROL SYSTEM WILL OPERATE UP TO 3 PUMPS & BLOWER

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | CS8600-A | CS8600-B | CS8600-C |
|------------|------------|------------|------------|
| PUMP 1 | 1 or 2 SPD | 1 or 2 SPD | 1 or 2 SPD |
| PUMP 2 | 1 or 2 SPD | 1 or 2 SPD | 1 or 2 SPD |
| PUMP 3 | 1 SPD | 1SPD | 1SPD |
| BLOWER | YES | YES | YES |
| OZONE | YES | YES | YES |
| HEATER | 11KW | 5.5KW | N/A* |
| LIGHT | 12/120V | 12/120V | 12/120V |
| *Gas Ready | | | |

ALL CIRCUITS ARE CONVERTIBLE TO 120 OR 240VAC

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12 LIGHT | 1A | |
| HEATER | 23A/46A | |

SYSTEM DIMENSIONS

22"Hx19.5"Wx10"D w/Short Base

Shipping Weight:

32.5 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS



Standard:

- 1.375/5.5KW Heater Assembly
- 2 Speed Pump (various HP & voltages)
- Blower, 1 HP, 120V
- 24hr Timer with Mode Switch
- Full Range Thermostat
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty

Exclusive:

- "VDS" Visual Diagnostics
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening

CONTROLLER OPTIONS



All Hydro-Quip Aire control systems are spaside controller ready.

SYSTEM DIMENSIONS:

18" L x 15" H x 15" D

Shipping Weight:

58.7 LBS

ES4000 Series Air Equipment System

The Hydro-Quip ES4000 series equipment system represents the finest in classic Electro Mechanical dependability. By taking our compact CS4000 series and adding a pump and blower, gives you the benefit of having a complete spa control system in one convenient package. The durability of the components used in our mechanical controls is legendary and Hydro-Quip spares no expense at equipping our controls with the best available.

From the ease of installation to inclusion of our exclusive Visual Diagnostic System to aid in trouble shooting you and your customers will be glad you made the "Smart Choice" and chose to equip your spas with a system manufactured by Hydro-Quip the industries oldest and most trusted supplier.

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | ES4000-U1 | ES4000-U2 |
|-----------|-----------|-----------|
| PUMP 1 | 2 SPD | 2 SPD |
| PUMP 2 | N/A | 1 SPD |
| BLOWER | YES | YES |
| OZONE | YES | YES |

See chart below for Pump and Blowers options

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------|--------------|--|
| PUMP | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |

Equipment System Component Options Chart

| Option* Code | Pump | Voltage | Blower | Voltage |
|-----------------|--------|---------|--------|---------|
| -A | 1 HP | 120 | 1 HP | 120 |
| -C | 1.5 HP | 120 | 1 HP | 120 |
| -C-5 | 1.5 HP | 240 | 1 HP | 120 |
| -E | 2 HP | 240 | 1 HP | 120 |
| -G | 3 HP | 240 | 1 HP | 120 |
| -J | 4 HP | 240 | 1 HP | 120 |

*Add Option Code to the ES model number

Equipment Systems also available without blowers, call for details.



Standard:

- 1.375/5.5KW Heater Assembly
- 2 Speed Pump (various HP & voltages)
- Blower, 1 HP, 120V
- 24hr Timer with Mode Switch
- Full Range Thermostat
- Ozone circuit (120V/240V)
- Light Circuit (12V)
- 1 Year Warranty

Exclusive:

- "VDS" Visual Diagnostics
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening

CONTROLLER OPTIONS



All Hydro-Quip Aire control systems are spaside controller ready.

SYSTEM DIMENSIONS:

21 ½" L x 11" H x 15" D

Shipping Weight:

58.7 LBS

ES6000 Series Air Equipment System

The Hydro-Quip ES6000 series equipment system represents the finest in classic Electro Mechanical dependability. By taking our CS6000 series and adding a pump and blower, gives you the benefit of having a complete spa control system in one convenient package. The durability of the components used in our mechanical controls is legendary and Hydro-Quip spares no expense at equipping our controls with the best available.

From the ease of installation to inclusion of our exclusive Visual Diagnostic System to aid in trouble shooting you and your customers will be glad you made the "Smart Choice" and chose to equip your spas with a system manufactured by Hydro-Quip the industries oldest and most trusted supplier.

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | ES6000-U1 | ES6000-U2 |
|-----------|-----------|-----------|
| PUMP 1 | 2 SPD | 2 SPD |
| PUMP 2 | N/A | 1 SPD |
| BLOWER | YES | YES |
| OZONE | YES | YES |

See chart below for Pump and Blowers options

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------|--------------|--|
| PUMP | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |

Equipment System Component Options Chart

| Option* Code | Pump | Voltage | Blower | Voltage |
|-----------------|--------|---------|--------|---------|
| -A | 1 HP | 120 | 1 HP | 120 |
| -C | 1.5 HP | 120 | 1 HP | 120 |
| -C-5 | 1.5 HP | 240 | 1 HP | 120 |
| -E | 2 HP | 240 | 1 HP | 120 |
| -G | 3 HP | 240 | 1 HP | 120 |
| -J | 4 HP | 240 | 1 HP | 120 |

*Add Option Code to the ES model number

Equipment Systems also available without blowers, call for details.



Standard:

- 5.5KW Heater Assembly
 - 2 SPD Pump (various HP & voltage)
- 1 HP Blower, 120V
- Ozone circuit (120V/240V)
- 12V Light
- 1 Year Warranty

Exclusive:

- Smart-Freeze Protection
- Lighted Smart Cords
- "Paint-Lock" Rust Proof Enclosure
- Pressure Switch Protected
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

ES4000 Series Solid State Equipment System

The Hydro-Quip solid-state ES4000 series equipment system incorporates a pump and a blower with our newest solid state control system. The 4000 series offers our exclusive slide design which allows you to slide the control box up and down and also rotate from front to back. This innovative design makes the ES4000 series one of the most versatile systems on the market today.

From the ease of installation to inclusion of our exclusive features to aid in trouble shooting you and your customers will be glad you made the "Smart Choice" and chose to equip your spas with a system manufactured by Hydro-Quip the industries oldest and most trusted supplier.

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | ES4100 | ES4200 | ES4220 | ES4230 | ES4330 |
|-------------|------------|--------|--------|--------|--------|
| PUMP 1 | 1 OR 2 SPD | 2 SPD | 2 SPD | 2 SPD | 2 SPD |
| PUMP 2/BLWR | NA | 1 SPD | 2 SPD | 1 SPD | 2 SPD |
| PUMP 3/BLWR | NA | NA | NA | 1 SPD | 1 SPD |
| OZONE | YES | YES | YES | YES | YES |
| CIRC PUMP | NA | YES | NA | YES | YES |
| 12V LIGHT | YES | YES | YES | YES | YES |

See chart below for Pump and Blowers options

ELECTRICAL INPUT SPECIFICATION:

| SINGLE PHASE |
|--------------|
| 120/240VAC |
| 50/60HZ |

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |

KEYPAD OPTIONS







ECO-5 Keypad (ES4100) HQ PT#: 34-0207

ECO-3 Keypad (ES4230, ES4330) HQ PT#: 34-0197 ECO-6 Keypad (ES4200, ES4220) HQ PT#: 34-0208

All Hydro-Quip control systems include a keypad by default. If a different keypad is desired options may be available, please contact your Hydro-Quip representative for more details.

SYSTEM DIMENSIONS:

18" L x 15" H x 15" D

Shipping Weight:

58.7LBS

Equipment System Component Options Chart

| Option* Code | Pump | Voltage | Blower | Voltage |
|-----------------|--------|---------|--------|---------|
| -A | 1 HP | 120 | 1 HP | 120 |
| -C | 1.5 HP | 120 | 1 HP | 120 |
| -C-5 | 1.5 HP | 240 | 1 HP | 120 |
| -E | 2 HP | 240 | 1 HP | 120 |
| -G | 3 HP | 240 | 1 HP | 120 |
| -J | 4 HP | 240 | 1 HP | 120 |

*Add Option Code to the ES model number

Equipment Systems also available without blowers, call for details.



Standard:

- 5.5KW Heater Assembly
- 2 SPD Pump (various HP & voltage)
- 1 HP Blower, 120V
- Ozone circuit (120V/240V)
- 12V Light
- 1 Year Warranty

Exclusive:

- Smart-Freeze Protection
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Pressure Switch Protected
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

ES6000 Series Solid State Equipment System

The Hydro-Quip solid-state ES6000 series equipment system incorporates a pump and a blower with our most economical in solid state controls. This system represents the finest in equipment systems on the market today. No other manufacturer's equipment systems offer such an extensive array of available options or provides the same level of time and money saving features.

From the ease of installation to inclusion of our exclusive features to aid in trouble shooting you and your customers will be glad you made the "Smart Choice" and chose to equip your spas with a system manufactured by Hydro-Quip the industries oldest and most trusted supplier.

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | ES6100 | ES6200 | ES6220 | ES6230 | ES6330 |
|-------------|------------|--------|--------|--------|--------|
| PUMP 1 | 1 OR 2 SPD | 2 SPD | 2 SPD | 2 SPD | 2 SPD |
| PUMP 2/BLWR | NA | 1 SPD | 2 SPD | 1 SPD | 2 SPD |
| PUMP 3/BLWR | NA | NA | NA | 1 SPD | 1 SPD |
| OZONE | YES | YES | YES | YES | YES |
| CIRC PUMP | NA | YES | NA | YES | YES |
| 12V LIGHT | YES | YES | YES | YES | YES |

See chart below for Pump and Blowers options

ELECTRICAL INPUT SPECIFICATION:

| SINGLE PHASE |
|--------------|
| 120/240VAC |
| 50/60HZ |

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWER | 8A | |
| OZONE | 2A | |
| 12 LIGHT | 1A | |
| HEATER | 23A | |

KEYPAD OPTIONS







ECO-5 Keypad (ES6100)

ECO-3 Keypad (ES6230, ES6330) HQ PT#: 34-0197 ECO-6 Keypad (ES6200, ES6220)

All Hydro-Quip control systems include a keypad by default. If a different keypad is desired options may be available, please contact your Hydro-Quip representative for more details.

SYSTEM DIMENSIONS:

21 ½" L x 11" H x 15" D

Shipping Weight:

58.7LBS


Equipment System Component Options Chart

| Option* Code | Pump | Voltage | Blower | Voltage |
|-----------------|--------|---------|--------|---------|
| -A | 1 HP | 120 | 1 HP | 120 |
| -C | 1.5 HP | 120 | 1 HP | 120 |
| -C-5 | 1.5 HP | 240 | 1 HP | 120 |
| -E | 2 HP | 240 | 1 HP | 120 |
| -G | 3 HP | 240 | 1 HP | 120 |
| -J | 4 HP | 240 | 1 HP | 120 |

*Add Option Code to the ES model number

Equipment Systems also available without blowers, call for details.





ES9700 Series Solid State Equipment System

The Hydro-Quip solid-state ES9700 series equipment system incorporates a pump and a blower with our finest in solid state controls. This system represents the finest in equipment systems on the market today. No other manufacturer's equipment systems offer such an extensive array of available options or provides the same level of time and money saving features.

From the ease of installation to inclusion of our exclusive features to aid in trouble shooting you and your customers will be glad you made the "Smart Choice" and chose to equip your spas with a system manufactured by Hydro-Quip the industries oldest and most trusted supplier.

FEATURES & OPTIONS

Standard:

- 5.5KW Heater Assembly
- 2 Speed Pump (various HP & Voltage)
- 1 HP Blower, 120V
- HT-2 Spaside Control, 10' Cord
- Ozone circuit (120V/240V)
- 12V Light
- 1 Year Warranty

Exclusive:

- Smart-Freeze Protection
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Pressure Switch Protected
- Detailed Owners Manual
 - Detailed Wiring Diagram

Available Options:

- High Current GFCI
- Custom Faceplate Silk Screening
- Custom keypad labels available

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | ES9700 | |
|-------------------|------------|--|
| PUMP 1(Included) | 1 or 2 SPD | |
| PUMP 2 | 1 or 2 SPD | |
| PUMP 3 | 1 SPD | |
| AUX CIRCUIT (S) | 2 | |
| BLOWER(Included)* | 1-3 SPD | |
| OZONE | YES | |
| CIRC PUMP | YES | |
| 12V LIGHT | 1-3 STEP | |

See chart below for Pump and Blowers options

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| C | CIRCUIT(S) | MAXIMUM AMPS |
|---|------------|--------------|
| F | PUMP(S) | 13A |
| В | BLOWER | 8A |
| C | DZONE | 2A |
| 1 | 2 LIGHT | 1A |
| H | IFATER | 23A |

KEYPAD OPTIONS



Equipment System Component Options Chart

| Option* Code | Pump | Voltage | Blower | Voltage |
|-----------------|--------|---------|--------|---------|
| -A | 1 HP | 120 | 1 HP | 120 |
| -C | 1.5 HP | 120 | 1 HP | 120 |
| -C-5 | 1.5 HP | 240 | 1 HP | 120 |
| -E | 2 HP | 240 | 1 HP | 120 |
| -G | 3 HP | 240 | 1 HP | 120 |
| -J | 4 HP | 240 | 1 HP | 120 |

*Add Option Code to the ES model number

Equipment Systems also available without blowers, call for details.

SYSTEM DIMENSIONS:

21 ½" L x 14 ½" H x 15" D

Shipping Weight:

60.1LBS





ES8000 Series Solid-State Outdoor Equipment System

The Hydro-Quip solid-state ES8000 series equipment system represents the finest in outdoor systems on the market today. No other manufacturer's outdoor equipment systems offer such an extensive array of available options or provides the same level of time and money saving features.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

FEATURES & OPTIONS

Standard:

- **Outdoor Weather-tight Construction**
- 5.5/11KW Heater Assembly
- Electric or Gas ready
- Ozone circuit (120V/240V)
- Light Circuit (120V/12V)
- 1 Year Warranty

Exclusive:

- Smart-Freeze Protection
- HT-2 Spaside Control, 25' Cord
- Lighted Smart Cords
- "Paint-Lock" rust proof enclosure
- Pressure and Flow Switch Protected
- **Detailed Owners Manual**
- **Detailed Wiring Diagram**

Available Options:

- Custom Faceplate Silk Screening
- Custom keypad labels available

SUPPORTED PERIPHERALS BY MODEL

| COMPONENT | ES8650-A | ES8650-C | ES8650-D | ES8650-F | ES8650-G | ES8650-J |
|------------------|----------|----------|----------|----------|----------|----------|
| PUMP 1(Included) | 1.5HP | 2.5HP | 1.5HP | 2.5HP | 1.5HP | 2.5HP |
| PUMP 2 | 2 SPD |
| PUMP 3 | 1 SPD |
| BLOWER(Included |) 1.5HP | 1.5HP | 1.5HP | 1.5HP | 1.5HP | 1.5HP |
| OZONE | YES | YES | YES | YES | YES | YES |
| HEATER | 11KW | 11KW | 5.5KW | 5.5KW | N/A* | N/A* |
| LIGHT | 12/120V | 12/120V | 12/120V | 12/120V | 12/120V | 12/120V |
| | | | | | | |

ELECTRICAL INPUT SPECIFICATION:

SINGLE PHASE 120/240VAC 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

| CIRCUIT(S) | MAXIMUM AMPS | |
|------------------|--------------|--|
| PUMP(S) | 13A | |
| BLOWÈŔ | 8A | |
| OZONE | 2A | |
| CIRCULATION PUMP | 5A | |
| 12 LIGHT | 1A | |
| HEATER | 23A/46A | |

KEYPAD OPTIONS







HTII 10 Button Keypad (Included) HQ PT#: 34-0190A



IR Remote

SYSTEM DIMENSIONS:

26"Hx36"Wx18"D

Shipping Weight:

101 LBS (2 boxes)

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK) INDIVIDUAL (PLAIN/GENERIC) INDIVIDUAL (CUSTOM) FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





Standard:

- 5.5 or 11KW Heater Assembly
- 2.25" High Flow U-Shaped Heater Housing
- Stainless Steel Heater Housing
- Full Range Thermostat
- High Limit and Pressure Switch Protected
- 2"/1 ½" Plumbing Connections
- Weather-Tight Construction
- UL Listed
- 1 Year Warranty

Exclusive:

- Heater "ON" Indicator Light
- "Paint-Lock" rust proof enclosure
- Detailed Owners Manual
- Detailed Wiring Diagram

Available Options:

- Custom Faceplate Silk Screening
- Various Heater Wattages

HEATMAX Series Remote Heater System

The Hydro-Quip HEATMAX series heater is our basic "heater in a box" unit. When all you need is heat, this is the most practical and user friendly unit in the industry. 5.5kW OR 11kW for new and existing applications where a full 2" high flow free standing heater is needed.

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment produced by Hydro-Quip, the industries oldest and most trusted manufacturer.

AVAILABLE MODELS

| MODEL | HEATMAX RHS 5.5 | HEATMAX RHS 11 | |
|---------|-----------------|----------------|--|
| Voltage | 240 | 240 | |
| Wattage | 5.5kW | 11kW | |
| | | | |

ELECTRICAL INPUT SPECIFICATION:

| SINGLE PHASE |
|--------------|
| 120/240VAC |
| 50/60HZ |

SYSTEM DIMENSIONS:

15"L x 12"H x 4"D

SYSTEM WEIGHT:

16.4 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
CELL/BULK PACK (16, 32, 64, 128+)
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS





FEATURES

- New Innovative Design
- Quiet Operation
- Compact and Lightweight
- Thermally Protected
- Various Cord Options
- Available In Various Voltages and HP's
- · Custom Private Labeling Available
- Export Models Available

SILENT AIRE BLOWER SERIES

Hydro-Quip introduces our *SILENT AIRE* blower series. This innovative, compact and sleek design make this the most practical blower on the market today. With its quiet operation and universal cord configurations*, the *SILENT AIRE* blower was engineered to perform above all the rest!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment manufactured by Hydro-Quip, the industries oldest and most trusted supplier.

AVAILABLE MODELS

| | ODEL MBERS | 994-55002-7A-S | 994-55102-7A-S | 994-56002-7C-S | 994-56102-7C-S |
|---|---------------|-------------------|----------------|----------------|----------------|
| ı | VOLTS | 120 | 240 | 120 | 240 |
| | HP | 1.0 | 1.0 | 1.5 | 1.5 |
| | SPEED | 1 | 1 | 1 | 1 |
| ı | Export n | nodels also avail | lable | | |

ELECTRICAL INPUT SPECIFICATION:

| SINGLE PHASE |
|--------------|
| 120/240VAC |
| 50/60HZ |

BLOWER DIMENSIONS:

9.25"L X 5"H X 8"W

SHIPPING WEIGHT:

5.8 LBS


PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)
BULK PACK 12 INDIVIDUALLY BOXED OR LOOSE IN MASTER CARTON
CELL PACK LOOSE 96 OR 192 UNITS PER
FOB CORONA, CA 92880

WARRANTY:

1 YEAR WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

CORD OPTIONS







UNIVERSAL RITE-FIT HEATER ASSEMBLY

Hydro-Quip introduces our new universal *RITE FIT* heater assembly. This innovative design allows you to use the *RITE FIT* heater to replace many on the market today. Save on inventory and save space, no need to carry so many different models when you only need one, the *RITE FIT* universal heater!

From the ease of installation to the efficiency of our products, your customers will be glad you made the "Smart Choice" and chose equipment manufactured by Hydro-Quip, the industries oldest and most trusted supplier.

FEATURES

- Universal 15" length (others available)
- · 2.0 5.5kW elements available
- Adjustable mounting and grounding studs
- Adjustable sensor cover plate
- Multiple pressure switch ports
- · Flush mount pressure switch port plugs
- · 2" Tailpieces and gaskets

AVAILABLE MODELS

| | 48-1540-RS | 48-1545-RS | 48-1555-RS |
|--------|------------|------------|------------|
| kW | 4.0 | 4.5 | 5.5 |
| Size | 2" | 2" | 2" |
| Length | 15" | 15" | 15" |
| | | | |

Export models also available

DIMENSIONS:

15" X 2.25"

SHIPPING WEIGHT:


3.5 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)
INDIVIDUAL (PLAIN/GENERIC)
INDIVIDUAL (CUSTOM)

WARRANTY:

1 YEAR "PARTS ONLY" WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS.



Hydro-Quip Limited Warranty

Distributor's Choice

Air Switch Series Controls / Equipment

Effective January 1, 2009

Model/Series

500, 700, 800, 1 Year

4000, 6000, 7000, 9000

Solid State Series Controls / Equipment

Effective January 1, 2009

Model/Series

 4000, 6000, 7000
 2 Year

 9700
 3 Year

 8600, 8648, 8650
 3 Year

HeatMax RHS Heaters

Effective January 1, 2009

Model/Series

HeatMax RHS Series 2 Year

Silent Aire Series Air Blowers

Effective January 1, 2009

All Models 1 Year

Warranty Procedure

Simply return the defective component to Hydro-Quip and we will evaluate your claim within the terms of the warranty and either replace or issue credit for the component. Please contact our customer service department for a Return Goods Authorization (RGA) and return freight prepaid.

See the Hydro-Quip Limited Warranty information noted above for length of coverage and for further details see below on the Controls & Equipment Systems warranty coverage.

For additional Service Information simply contact the Hydro-Quip Customer Service Dept. at Tel: 951.273.7575 or Fax: 951.273.7550

Hydro-Quip warrants its Controls & Equipment to the original purchaser to be free from defects in material and workmanship for the period noted ABOVE from the date of purchase, except as noted below. Products which become defective within the warranty period will be repaired or replaced (at the option of Hydro-Quip) except for damage to the System, Spa or other Structures related to freezing, water chemistry, negligence, abuse, misuse, misapplication, unauthorized modification, improper installation, normal wear and tear or chemical attack. This warranty extends only to normal, personal (non-commercial) usage by the original retail purchaser. Pump seals, o-rings, gaskets, air blower brushes and some spa side remote controls may only be covered during the first year of the warranty period.

Hydro-Quip will not be responsible for labor incurred in removing, inspecting and reinstalling of warrantable products for the period noted ABOVE or any travel related charges or labor costs attributable to disassembly and reassembly of the spa, skirt, decking or any other materials enclosing the System, or attributable to difficulties in gaining access to the System. Hydro-Quip will not be responsible for labor costs for routine maintenance, adjustments or alterations to the calibration of electrical devices.

Any products which are claimed to be defective must be shipped freight prepaid to Hydro-Quip and the repaired or replaced product will be returned to the sender freight collect. When sent to Hydro-Quip, the product must be accompanied by the sales receipt or other proof of the purchase date as well as the sender's name, mailing address, daytime phone number and any other information relating to this claim.

Unless state law expressly provides otherwise, Hydro-Quip will only be responsible for repair or replacement of any of its products that are found to be defective as provided above, and will not bear the cost of any consequential damages. This warranty gives you specific legal rights but you may have other rights which vary from state to state.



510A N. SHERIDAN ST. - CORONA, CA 92880 (PH) 951-273-7575 - (FAX) 800-332-7190 WEB: WWW.HOTWATERCONTROLS.COM