

Residential Ladder



- Tubing: 1.90" OD
- Wall Thickness: .049"
- Type: 304, 316L* stainless steel
- Bends: 6" Radius
- Elite model: LTDF-103 treads, Econoline model: LTDF-101 treads
- Anchors and escutcheons sold separately

| Econoline Model | Shipping Wt. | Elite Model | Shipping Wt. | Description | L | W | H |
|-----------------|--------------|-------------|--------------|---------------|-----|-----|----|
| RLF-24E-2A | 21 lbs. | RLF-24S-2A | 22 lbs. | 2-step ladder | 60" | 28" | 2" |
| RLF-24E-3B | 24 lbs. | RLF-24S-3B | 25 lbs. | 3-step ladder | 65" | 28" | 2" |
| RLF-24E-4C | 29 lbs. | RLF-24S-4C | 30 lbs. | 4-step ladder | 82" | 28" | 2" |
| RLF-24E-5D | 32 lbs. | RLF-24S-5D | 33 lbs. | 5-step ladder | 90" | 28" | 2" |

*Marine Grade, add -MG to part number when ordering. REQUIRED for Salt Pools.

Note: Frames extend 6 1/2" from the pool wall. Frame is secured to pool deck with two anchor sockets on 20" centers (elite), or 19" centers (econoline). Lower end of frame is bent to meet pool wall and fitted with two white rubber bumpers.

