

McGrayel Company, Inc. EasyCare® Products div. 5261 S. VIIIa Ave. P.O. Box 12362 Fresno, CA 93725 U.S.A.

Tel. Direct: 1-559-299-7660

Material Safety Data Sheet

Toll-Free 1-800-289-7660 (U.S.A.)

SECTION I • PRODUCT IDENTIFICATION

Trade Name: Scaletec Plus®

Calcium Descaler, Inhibitor and Stain Remover

Product Code: #20064
MSDS Date: 11-29-2011
Supersedes: 09-13-2001
CAS Number: Proprietary
OSHA Hazard: None

DOT Hazard Class: Non-hazardous

NFPA Designation


Hazard Rating: 4 = Severe

3 = Serious

2 = Moderate

1 = Slight

0 = Minimal



SECTION II • HAZARDOUS INGREDIENTS

Ingredient Information:

Components of this product comprises proprietary trade secret information.

SECTION III • PHYSICAL CHARACTERISTICS

PHYSICAL FORM: Liquid

COLOR: reddish-pink color
ODOR: Very slight odor
pH (as is): 11.5 to 11.7

BOILING POINT: > 100 °C (> 212 °F)

MELTING POINT: Below 0 °C SPECIFIC GRAVITY: 1.094 @ 20 °C

SOLUBILITY IN WATER: Miscible water in all proportions

EVAPORATION RATE: < 1

VAPOR PRESSURE: Not relevant

SECTION IV • FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not applicable

FLAMMABLE LIMITS: Lower: N/A Upper: N/A

EXTINGUISHING MEDIA: Water fog, foam, CO₂ and dry chemicals

SPECIAL FIRE FIGHTING

PROCEDURES: None UNUSUAL FIRE HAZARDS: None

STABILITY: Stable INCOMPATIBILITY: None

HAZARDOUS DECOMPOSITION

PRODUCTS: None

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI • HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: Eye contact, skin contact, and ingestion.

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

Acute Effects Of Exposure:

1. Eye Contact: Probable eye irritant. Effects may range from mild to severe depending on the length

of exposure, solution concentration and first aid measures.

2. Skin Contact: Minimal skin irritation is expected. Effects may vary depending on the length

of exposure, solution concentration and first aid measures.

3. Ingestion: May be harmful. Liquid may cause mouth and throat irritation resulting in nausea,

vomiting and/or abdominal pain. No data is available on human ingestion.

Chronic Effects Of Exposure:

The effects from chronic exposure to this product have not been evaluated.

CARCINOGENICITY: No data is available

MEDICAL CONDITIONS

AGGRAVATED BY EXPOSURE: Persons with pre-existing eye conditions may be more susceptible

to the effects of overexposure to Scaletec Plus®.

EXPOSURE LIMITS: Not established for this product.

FIRST AID MEASURES:

EYE CONTACT: In case of contact, flush eyes with plenty of clean running water for up to several

minutes or longer until all traces of product are removed. Lifting the upper and lower lids occasionally. Remove contact lenses, if worn. Consult a physician if irritation persists.

SKIN CONTACT: In case of contact, flush skin with plenty of clean running water to remove all traces of

product. If necessary, remove and wash contaminated clothing and shoes. If a burn or

irritation occurs, call a physician.

INGESTION: If swallowed, DO NOT induce vomiting. Rinse with copious amounts of water or milk,

first. Irrigate the esophagus and dilute stomach contents by slowly giving one (1) or two (2) glasses of water or milk. Avoid giving alcohol or alcohol related products. In cases where the individual is semi-comatose, comatose or convulsing, DO NOT GIVE FLUIDS BY MOUTH. In case of intentional ingestion of the product seek medical

assistance immediately: take individual to pearset medical facility

assistance immediately; take individual to nearest medical facility.

STEPS TO BE TAKEN IN CSE MATERIAL IS RELEASED OR SPILLED:

Initially minimize area effected by the spill or leak. Block any potential routes to water systems (e.g., sewers, streams, lakes, etc.). Recover as much of the pure product as possible. Later, determine if this recovered **Scaletec Plus®** can be used for its intended purpose. Address clean-up of contaminated environments. Spill or leak residuals must be neutralized with dilute acid or absorbed onto inert substance. After all visible traces have been removed, flush area with a large amount of water. Generally, neutralized waste may be disposed into a municipal sewer system with a large amount of water. Disposal method must be made in accordance with federal, state, and local regulations.

Based on the products toxicological and chemical properties, and on the size and location of the spill or leak, assess the impact on contaminated environments (e.g., water systems, ground, air, equipment, etc.). Minimize adverse effects on these environments. Determine if federal, state, and/or local release notification is required.

WASTE DISPOSAL METHOD:

Follow federal, state, and local regulations governing the disposal of waste materials.

Spills or Leak Residuals, Contaminated Materials: Determine if waste containing this product can be handled by available effluent system or other on-site waste management unit (e.g. incinerator, deep well, etc.). If off-site management is required, contact a company experienced in industrial waste management.

Empty containers of this product <u>are not</u> hazardous wastes. Triple rinse container with water before discarding in the trash or offer for recycling.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep container closed when not in use. Keep product from freezing. Keep product away from children.

SECTION VIII • CONTROL MEASURES

RESPIRATORY PROTECTION: None required

VENTILATION: Normal room ventilation is preferable

EYE PROTECTION: Safety glasses preferred

PROTECTIVE GLOVES: None

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash

WORK / HYGIENIC PRACTICES: Handle in accordance with good hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing.

